

Print & Cut Inkjet Printer

CJV200 *series* -160 / -130 / -75

In Pursuit of High Image Quality and Ease of Use for Everyone



INK SAVING FUNCTION

Anyone can easily reduce ink consumption without technical expertise. This function is available with any media and profiles.

SIMPLE DESIGN SOFTWARE

SimpleCreate is software that allows you to create labels, POP, stickers, and other designs without a need of DTP software. It provides simple tools for creating designs and cutlines, as well as direct output from the software.

SINGLE PRINT HEAD

- Simple Maintenance

Single print head system contributes less cleaning time and adjustment time. The simple design allows you to work quickly and easily.

SPECIFICATIONS

		CJV200 -160	CJV200 -130	CJV200 -75
Item				
Print head		On-demand piezo head		
Print resolution		Y:600, 900, 1200dpi X:600, 1200dpi		
Head gap		2levels by manual (1.5mm / 2.0mm)		
Ink	Type	SS21、SS22、BS4		
	Color	4color(C,M,Y,K) 8color(C,M,Y,K,Lc,Lm,Lk,Or)		
	Capacity	440ml		
Ink circulation		Yes		
Max.Load capacity		1620mm(63.8in)	1371mm(54in)	810mm(31.9in)
Max.Printable width		1610mm(63.4in)	1361mm(53.5in)	800mm(31.5in)
Media roll outer diameter		φ180mm or less (7.1in)		
Media roll weight		25kg (55.1 lb.) or less		
Media roll inside diameter		2 / 3 inch		
Cut function	Cut speed / acceleration	Speed:Max.300 mm/s Acceleration:Max. 0.5G		
	Cut pressure	10-450gf		
	Cutter response times	10 times / sec		
	Cut speed / acceleration	±0.2 mm (Excluding expansion and contraction of film due to temperature)		
Interface		Ethernet 1000 BASE-TT(Recommended) / USB 2.0 Hi-speed		
Power		AC(100~120V/200~240V±10%)x2 50/60Hz±1Hz		
Power consumption		Max.1320W x2 / 4.5W or less (Sleep mode)		
Operational environment	Temperature	20 - 30 degC (68-86 degF)		
	Humidity	35 - 65% Rh (Non condensing)		
	Guaranteed accuracy temperature	20 - 25 degC (68 - 77 degF)		
	Dust level	Equivalent to general office		
Dimensions (WxDxH)		2,770mm x 748mm x 1,370mm (109 x 29 x 54 in)	2,520mm x 748mm x 1,370mm (99 x 29 x 54 in)	1,960mm x 748mm x 1,370mm (77 x 29 x 54 in)
Weight		140kg(309lb)	130kg(287lb)	105kg(231lb)



High Quality 1200x1200 6pass		10.1 m²/h (108.7 sqft/h)	5.0 m²/h (53.8 sqft/h)
Quality 900x1200 6pass		12.5 m²/h (134.5 sqft/h)	6.0 m²/h (64.6 sqft/h)
Standard 600x1200 6pass		17.0 m²/h (183.0 sqft/h)	8.5 m²/h (91.5 sqft/h)
High Speed 600x1200 4pass		22.0 m²/h (236.8 sqft/h)	11.0 m²/h (118.4 sqft/h)

*CJV200-160 print speed

■ 4 Color ■ 8 Color

Raster Link 7



Combination of upgraded usability and functionality
Improves reproducibility of special effects (such as transparency)
of PDF data

Increases RIP processing speed of PDF data by 25% on average
Prints out the variable data by Variable print function
Displays frequently used setting and pop-up windows

Mimaki Cloud Technology **PICT3**

Exclusively Distributed by:



MAKATI (HEAD OFFICE)

8837 Sampaloc St.,
San Antonio Village,
Makati City 1203
Contact No.:
890-2657 ; 896-6698 ;
896-8488
+63 917 623 5986

PANGASINAN

By-Pass Road.,
Brgy. Sto. Domingo,
Urdaneta City
Pangasinan
Contact No.:
+63 75 529 2367
+63 917 856 7255

CEBU

163 Sikatuna corner
Jakosalem St.,
Brgy., Zapatera
Cebu City
Contact No.:
(032) 412-5661

CAGAYAN DE ORO

Goking Bldg.,
San Pedro St.,
Gusa, CDO
Contact No.:
(088) 885 0410
+63 917 713 6083

ZAMBOANGA

35 A Villa Maria Drive,
Estrada St. Tetuan,
Zamboanga City
Contact No.:
+62 992 7156
+63 917 159 0677

DAVAO

Dasi Compound Water
District, Bajada,
Davao City
Contact No.:
+63 82 222 0921
+63 917 539 1104